Product Data Sheet





twinFLOORclick is a commercial grade, waterproof vinyl flooring range which is manufactured with a Uni-Clic tongue and groove profile, for quick and easy fitting.

	twin FLOOR click planks	twin FLOOR click tiles
Unit Size	1210 x 190 x 5.0mm	605 x 304 x 5.0mm
Units/pack	8	10
Pack Coverage	I.84m²	1.84m²
Weight	18.8kg	18.8kg

Wear Layer	0.5mm (commercial grade)
Coating	PU with ceramic beads
Edge	Bevelled
Slip Resistance - DIN 51130	RIO
Sound Reduction – EN712-2	5db
Utilisation Class – EN649	33/42
Residual Indentation – EN433	0.08mm
Chemical Resistance – EN423	Pass
Dimensional Stability – EN434	Pass
Antimicrobial Activity – ASTM G 21-96	Bfl-S1
Colour Fastness to Light – EN20105-B02	ISO 9000, ISO 14001
Wear resistance (Frick-Taber test) – EN660-2	Class 0
Content of formaldehyde – EN717-1	≥ 6
Initial Type Testing of Fire Behaviour	Bfl-S1
– EN ISO 9239-1	
Manufacturing Plant	ISO 9000, ISO 1400 I
Cleaning	twinFLOOR Polish and Cleaner is a 2-in I solution for protection and cleanliness