Safety Data Sheet (91/155/EEC)



Material: SUPERBOND High Modulus Silicone Transsucent 310ml

Version: 1.0 Date of last alteration: 16.06.2007

1 Identification of the substance/preparation and company

1.1 Identification of the substance or preparation:

Commercial Product Name: SUPERBOND High Modulus Silicone Sealant Transsucent 310ml

1.2 Company/undertaking identification:

Distributor:A.B Building Products LimitedStreet:Units 4&5, Regents Court

City:AndoverCode:HampshireSP10 5NX

Telephone: +44 (0)1264 359984 **Fax:** +44 (0)1264 335200

 Telefax
 Telephone

 Information:
 +44 (0)1264 335200
 +44 (0)1264 359984

2 Composition/information on ingredients

2.1 Chemical characterisation:

Chemical characteristics	
Mixture of Polydimethylsiloxanes, Amorphous Silica and cross-linkers.	

Hazardous ingredients (EU):

CAS-No.	Material	Content Warning Labo			g Label (EU)	
		from	until		Symbol	R-Phrases
64742-46-7	Distillates, Petroluem, Hydrotreated Middle		<15	%	Xn, -	R65
176689-77-9	Silianetriol, Ethyl-Triacetate		<2	%	Xn, C -	R14, R22, R34
4253-34-3	Silianetriol, Methyl-Triacetate		<2	%	Xn, C -	R14, R22, R34

3 Hazards identification

3.1 Critical hazards to man and environment:

	Main Hazzards	Description			
		-Silghtly irratating to eys, respriataury system and skin. After Drying may stick to skin			
3.2	Other Hazzards	ner Hazzards Description			
		- Conbustable.			
		On contact with humidity, irrating vapours are released. During use acetic acid is released.			
		Silghtly irratating to eys, respriataury system and skin.After Drying may stick to skin			
3.3	Other Hazzards	rds Description			
	Further information	-According to EC criteria, this product is not classified as a hazardous preparation.			

4 First-aid measures

- 4.1 Inhalation: Not specifically applicable
- **4.2 Skin contact:** After contact with skin, remove product mechanically. Wash off with soap and water.
- **4.3** Eye contact: Rinse immediately with plenty of water for 10-15 minutes and seek medical advice.
- **4.4 Ingestion:** Rinse moth with water. Don not induce vomiting. Consult a Physician if necessary.

.

Safety Data Sheet (91/155/EEC)



(DIN 51794)

Material: SUPERBOND High Modulus Silicone Transsucent 310ml

Version: 1.0 Date of last alteration: 16.06.2007

5 Fire-fighting measures

- **5.1 Suitable extinguishing media:** All standard extinguishing agents are sutable.
- 5.2 Fire fighting protection: Cool down containers exposed to heat with a water spray. Wear self contained breathing apparatus.

6 Accidental release measures

- **6.1 Personal precautions:** Ensure adequate ventilation. Do not breath vapours. Avoid contact with skin and eyes. Use personal protective equipment.
- 6.2 Environmental precautions: Product dose not present any paticular risk to the environment.
- **6.3 Methods for cleaning up:** Use mechanical handling equpment. Scrape up or shovel into suitable container for disposal. Absorb residue with sutable inert material. Decontaminate and wash floor with an appropriate solvent, then wash with plenty of water.

7 Handling and storage

- 7.1 Advice on safe handling: Work outside or in well ventilated area. Wear personal protective equipment.
- 7.2 Requirements for storage: Keep containers tightly closed in a dry, cool and well ventilated place.

8 Exposure controls / personal protection equipment

- **8.1 Hand protection advice:** There is no risk to health due to contact with the chemical. Use hand protection to prevent mechanical injuries.
- **8.2** Eye protection: Safety glasses with side-shields.
- 8.3 Hygiene Measures: Avoid contact with skin, eyes and colthing. Ensure adequate ventallation, especially in confined areas. Handle in accordance with good industrial hygiene and safty pratise. Wash hands before breaks and immediately after handling the product. When handling, do not eat, drink or smoke. Observe standard industrial hygiene practices for the handling of chemical substances. Do not eat, drink or smoke when handling.
- **8.4 Protective measures:** Wear sutable gloves and eye/face protection. In the event of insufficent ventilation, using a respiratory protective device with gas filter is recommended.
- 8.5 Occupational exposure limits: Acetic acid WEL: 10ppm(25mg/m₃) (8h TWA) WEL: 15ppm (37mg/m₃) (15mins STEL)

9 Physical and chemical properties

9.1 Appearance

Form.....: Thixotropic paste Colour.....: Translucent

Odour...... Perceptible oudor (like vinegar).

9.2 Safety data Method: (67/548/EEC):

Density...... approx.1,03 g/cm3 at 25 °C

Solubility in water.....: virtually insoluble pH-Value....: not applicable Thermal decomposition....: not applicable

10 Stability and reactivity

- **10.0 Stability:** Stable at room tempretures provided it is not in contact with air. Vulcanises at room temperature on contact with moisture in the air.
- 10.1 Conditions to avoid: No dangerous reactions known under normal conditions of use.
- **10.3 Hazardous decomposition products:** During vulcanisation, acetic acid is released (quanitity potentially released <3% off weight). On combustion, forms carbon oxides and amorphous silica.

Safety Data Sheet (91/155/EEC)



Material: SUPERBOND High Modulus Silicone Transsucent 310ml

Version: 1.0 Date of last alteration: 16.06.2007

11 Toxicological information

- 11.0 Acute toxicity: Not classified as harful by inhallation, by contact with skin of if swallowed.
- 11.2 Local effects: May be irrtating to the respiratory system (at high vapour concentrations)
- 11.3 Routes of exposure: Refer to section 4 of this MSDS for routes of exsporsure and corresponding symptoms.

12 Ecological information

- 12.1 Mobility: Ultimate destination of the product: Soil and sediment.
- 12.2 Bultimate Aerobic Biodegradability: Not biodegradable
- 12.3 Bioaccumilation: Petroleum distillate. Potentially bioaccumulable. Polydimethylsiloxane: Not bioaccumulable.
- **12.4 Ecotoxicity:** Not considered to be harmful to aquatic organisms. Not classified as dangerous for the environment, according to EC crireria.

13 Disposal considerations

- **13.1 Material Recommendation:** Dispose of according to regulations by incineration in a special waste incinerator. Small quantities may be disposed of in a domestic waste incinerator. Observe local bye-laws. After solidification, material can be stored together with domestic waste. Observe local bye-laws.
- **13.2 Contaminated packaging:** Completely discharge containers. Containers may be recycled or re-used. Observe local/national byelaws.

14 Transport information

14.1 Further information: This product is not regarded as dangerous goods according to the National and International regulations of dangerous goods and is not restricted for transport according to RID/ADR, IMO/IMDG, ICAO-IATO.

15 Regulatory information

- 15.1 Labelling According to Chemicals (Hazard information and packaging for supply)
- 15.2 Regulations 2002 CHIP3.1; Not applicable.
- **15.3** Further information: Not a hazardous substance or preparation according to EC directives 67/548/EEC or 1999/45/EC. No R or S phrases applicable

16 Other information

16.1 R-phrases, which are listed in section 2

R10 - Flammable.

R14 - Reacts violently with water.

R22 - Harmful if swallowed.

R34 - Causes burns.

R35 - Causes severe burns.

R45 – May cause cancer.

R65 - Harmful; may cause lung damage if swallowed.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of it's publication. The information given id designed only as a guidance foe safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the content of the Material Safety Data Sheet.