

Acrylic Caulk

Technical Data

Product Code 80

Form	Viscous paste hardening by evaporation of water to a semi - flexible solid.
Specific Gravity	1.61 - 1.66
pH	8.00 - 8.70
Flashpoint	None
Solids Content (%)	> 79
Application Temp. Range	+4 C to +30 C
Service Temp. Range	-15 C to +75 C
Durability	Up to 15 years when used as recommended.
Shelf Life	Up to 15 months when stored in unopened containers under cool dry conditions. AVOID FROST.
Compatibility	Can be used in contact with most building and decorating materials but should not be used against bituminous materials.
Limitations	Should not be used in conditions of continuous immersion, below ground level, in areas of high abrasion (e.g. floor joints).
Colour	As agreed with customer

NB. - This material may change colour upon drying to a slightly darker shade. It may therefore be prudent to try a small sample area prior to full production

Storage - A small amount of liquid may form on the surface of the material, this can be readily remixed by stirring. If the lid is left off the container for a period of time a skin will form over the material. This skin should be removed and not mixed into the product. (This does not apply to cartridge material)

Packaging - As specified by customer

Health and Safety - See the relevant Material Safety Data Sheet.

The information contained in this leaflet is given in good faith and is based on results gained from experience and tests. However all recommendations and suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the terms and conditions of sale, a copy of which is available on request.