



FROTH-PAK



FROTH-PAK

The foam machine in one kit

FROTH-PAK The foam machine in one kit

The FROTH-PAK advantage

FROTH-PAK™ is a portable two component polyurethane spray foam kit which enables the professional to produce polyurethane foam of exceptionally high quality, quickly and easily, wherever and whenever required.

FROTH-PAK is intended for use as foamed-in-place sealant for air leakage control and insulation of gaps, cracks, cavities and joints in the building envelope.

It is used for sealing ducts, elbows, valves, tees, and boxes, replacing or repairing insulation in refrigerated containers and refrigerated warehouses. FROTH-PAK is used around door and window perimeters, roof/wall intersections, and the sealing of mechanical, electrical and plumbing penetrations in walls, floors, ceilings, attics and roofs. FROTH-PAK adheres to most surfaces including wood, metal, masonry, glass, and most plastics.

The FROTH-PAK kit comprises two pressurised tanks, linked by hoses, to a dispensing gun. When the contents of the two tanks are dispensed, they chemically react to produce a froth-like substance, which quickly expands to about three to five times the dispensed volume.

The foam solidifies in about 60 seconds and fully cures into a solid permanent structure in approximately five minutes. Cured foam resists moisture, insulates, dampens noise, adds structural support, provides an air-seal and fills voids.

Pistola aplicadora

The new redesigned INSTA-FLO™ Gun is a sturdy, reusable, patented, lightweight plastic gun with a comfortable grip. Flow rate is easily controlled by means of a touch sensitive trigger. Precise metering reduces overspray and waste. A safety mechanism protects against accidental discharge. An ejector clip makes changing nozzles a simple operation.



Anti-crossover dispensing nozzles

The new anti-crossover nozzles eliminate chemical crossover by means of a unique patented internal check valve. A clear dispensing tip allows applicator to see if the nozzle has been used and a new tapered design improves the foam mix. Side wings make nozzle attachment quick and easy. Pre-attached, long flexible hoses are supplied for quicker start-up and greater mobility for the operator. No external power source is required and application is quick, easy and labour saving.



WORKING TEMPERATURE RANGE +5 °C - +25 °C

FROTH-PAK The foam machine in one kit


Pulverization nozzle



Gmid 259212
yellow/green

Caulking Low output, controlled bead size


- >>> Designed for precisely controlled output
- >>> Ideal for tight areas
- >>> Minimizes overspray and waste



Gmid 259216
white/blue

Fan/Spray Medium output, wide area coverage


- >>> Ideal for flat applications: walls, roofs and ceilings
- >>> Smooth finish



Gmid 259219
white/transparent

NS Cone/Spray Medium output, small area coverage

- >>> Cylindrical spray pattern
- >>> Fills voids or cavities



Gmid 259220
black/transparent

Pour Nozzle High output, large volume coverage

- >>> Ideal for filling large cavities (slow rise formulation recommended)
- >>> Use in hidden cavity applications

| DESCRIPTION | Cylinder | | | Polyurethane foam | | | |
|---|-----------------|--------------------|-----|-------------------|-------------|---------------------|------------------------|
| | NET WEIGHT (KG) | PRESSURE VALUE BAR | | DENSITY (kg/m³) | YIELD* (m²) | RISE TIME (Seconds) | FIRE RATING DIN 4102-1 |
| | | POLYOL | ISO | | | | |
| FROTH-PAK™ 180 kit QR (GMID# 248474) (Quick Rise) (Tank Only) | 11.88 | 14.5 | 16 | 30 | 0.40 | 30 | B2 |
| FROTH-PAK™ 180 kit SR (GMID# 248471) (Slow Rise) (Tank Only) | 11.88 | 14.5 | 16 | 30 | 0.40 | 60 | B2 |
| FROTH-PAK™ 600 Polyol QR (GMID# 247779) (Quick Rise) (Tank Only) | 19.90 | 14.5 | | 30 | 1.40 | 30 | B2 |
| FROTH-PAK™ 600 Isocyanate (GMID# 248197) (Quick Rise) (Tank Only) | 20.50 | | 16 | | | | |
| FROTH-PAK™ 600 Polyol SR (GMID# 248246) (Slow Rise) (Tank Only) | 19.90 | 14.5 | | 30 | 1.40 | 60 | B2 |
| FROTH-PAK™ 600 Isocyanate (GMID# 248197) (Slow Rise) (Tank Only) | 20.50 | | 16 | | | | |

* Theoretical yield calculations are done in perfect laboratories conditions, without taking into account the loss of blowing agent or the variations in application methods and types. Example of yield: 1 m³ allows to 20m² with a 50mm foam thickness

FROTH-PAK APPLICATIONS

AGRICULTURE

- >>> Grain storage bin sealant
- >>> Silo sealant

AIR-SEALING

- >>> Around doors and windows
- >>> Roof and wall joints penetrations

COLD STORAGE

- >>> Ceiling, wall and floor seams
- >>> Corrugated roof decks

COMMERCIAL VEHICLES

- >>> Insulation
- >>> Sound dampening
- >>> Vibration control
- >>> Surface protection
- >>> Sealant against air, water & dust

HEATING AND VENTILATING

- >>> Duct sealant
- >>> Geothermal pipe insulator

INSULATION

- >>> Stud wall cavity fill

PLUMBING

- >>> Structural support
- >>> Around copper or PVC

POOLS AND SPA

- >>> Sound dampening
- >>> Insulation repair

THEATRE

- >>> Stage and movie sets
- >>> Floats

WHY USE FROTH-PAK?

The foam machine in one kit

- >>> Convenient and easy to use
- >>> Dispenses, expands and becomes tack free in seconds
- >>> Cut, sand and paint in minutes
- >>> Great flow control, less waste
- >>> Excellent for filling hard to reach areas and irregular surfaces
- >>> Kits are portable and self-contained—ready to use in minutes
- >>> High thermal resistance
- >>> Foam bonds to most surfaces
- >>> Minimal operator training, no other equipment needed
- >>> Seals completely to improve air tightness
- >>> Keeps out smoke, odor, and moisture
- >>> Wide range of specialized dispensing nozzles

Note:

The information and data contained in this brochure do not represent exact sales specifications. The features of the products mentioned may vary. The information contained in this document has been provided in good faith, however it does not imply any liability, guarantee or assurance of product performance. It is the purchaser's responsibility to determine whether these Dow products are suitable for the application desired and to ensure that the site of work and method of application conform with current legislation. No licence is hereby granted for the use of patents or other industrial or intellectual property rights. If Dow products are purchased, we advise following the most up-to-date suggestions and recommendations.

Distributor