

Printing date 15.03.2013 Version number 3 Revision: 29.11.2011

# 1 Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: illbruck FM617

· MSDS code: A-I-FM617

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation Sealant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Tremco illbruck Productie B.V. Vlietskade 1032, 4241 WC Arkel

T: +31 (0) 183568000, F: +31 (0) 183568100

msds@tremco-illbruck.com

#### · Further information obtainable from:

Tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

### · 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times please contact your national poisoning centre.

#### 2 Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

Harmful by inhalation. Limited evidence of a carcinogenic effect. Harmful: danger of R20-40-48/20:

serious damage to health by prolonged exposure through inhalation.

Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

F+; Extremely flammable

R12: Extremely flammable.

R53-64: May cause long-term adverse effects in the aquatic environment. May cause harm

to breastfed babies.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)





Printing date 15.03.2013 Version number 3 Revision: 29.11.2011

Trade name: illbruck FM617

(Contd. of page 1)

#### · 2.2 Label elements

#### · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

### · Code letter and hazard designation of product:

Xn Harmful

F+ Extremely flammable

### · Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues

# · Risk phrases:

12 Extremely flammable.

20 Harmful by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

40 Limited evidence of a carcinogenic effect.

42/43 May cause sensitisation by inhalation and skin contact.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

May cause long-term adverse effects in the aquatic environment.

May cause harm to breastfed babies.

# · Safety phrases:

- 2 Keep out of the reach of children.
- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe vapour/spray.
- 36/37 Wear suitable protective clothing and gloves.
- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 51 Use only in well-ventilated areas.

# · Special labelling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

- · Classification in accordance with Directive 75/324/EEC: Extremely flammable
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description: Active substance with propellant

(Contd. on page 3)



Printing date 15.03.2013 Version number 3 Revision: 29.11.2011

Trade name: illbruck FM617

	(Co	ntd. of page 2)
· Dangerous componer	nts:	
CAS: 9016-87-9 EINECS: 202-966-0	diphenylmethanediisocyanate,isomeres and homologues  Xn R20-40-48/20; Xn R42/43; Xi R36/37/38  Carc. Cat. 3  ♣ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;  ↑ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;  Skin Sens. 1, H317; STOT SE 3, H335	30- <50%
CAS: 85535-85-9 EINECS: 287-477-0	alkanes, C14-17, chloro  N R50/53 R64-66  Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362	5- <10%
CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether ► R12 ♦ Flam. Gas 1, H220; ♦ Press. Gas, H280	5- <10%
CAS: 75-28-5 EINECS: 200-857-2	isobutane ▶ F+ R12 ♦ Flam. Gas 1, H220; ♦ Press. Gas, H280	5- <10%
CAS: 74-98-6 EINECS: 200-827-9	propane ► F+ R12 ◆ Flam. Gas 1, H220; ← Press. Gas, H280	5- <10%
CAS: 1244733-77-4 EC number: 911-815-4	tris(2-chloro-1-methylethyl)phosphate  Xn R22  ♦ Acute Tox. 4, H302	1- <5%

#### · Additional information:

While curing the following substances are formed and released by a reaction with atmospheric humidity:

Carbon dioxide

For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

- · 4.1 Description of first aid measures
- · General information: Take affected persons out of danger area and lay down.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If symptoms persist consult doctor.

#### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.

(Contd. on page 4)



Printing date 15.03.2013 Version number 3 Revision: 29.11.2011

Trade name: illbruck FM617

(Contd. of page 3)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# 5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Carbon monoxide (CO)

Carbon dioxide

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (HCN)

- 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.

#### 6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Store away from water.
- · Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

(Contd. on page 5)





Printing date 15.03.2013 Version number 3 Revision: 29.11.2011

Trade name: illbruck FM617

(Contd. of page 4)

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

# 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen; as -NCO

# 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

· Protection of hands:



Protective gloves

- Material of gloves PE gloves
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Natural rubber, NR

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

PE gloves

(Contd. on page 6)



Printing date 15.03.2013 Version number 3 Revision: 29.11.2011

Trade name: illbruck FM617

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

۵	Dh	eical	and	chai	mical	nron	erties
IJ		/SiCai	anu	CHE	IIICai	prop	ei ues

3 Filysical and chemical properties			
<ul> <li>9.1 Information on basic physical and chemical properties</li> <li>General Information</li> <li>Appearance:</li> </ul>			
Form:	Aerosol		
Colour:	According to product specification		
· Odour:	Characteristic		
· Odour threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
Melting point/Melting range:	Not applicable, as aerosol.		
Boiling point/Boiling range:	Not applicable, as aerosol.		
· Flash point:	-97℃		
· Flammability (solid, gaseous):	Not applicable.		
· Ignition temperature:	235℃		
· Decomposition temperature:	Not determined.		
· Self-igniting:	Product is not selfigniting.		
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.		
· Explosion limits:			
Lower:	3.0 Vol %		
Upper:	18.6 Vol %		
· Vapour pressure at 20℃:	5200 hPa		
· Density at 20℃:	0.96 g/cm <sup>3</sup>		
· Relative density	Not determined.		
· Vapour density	Not determined.		
Evaporation rate	Not applicable.		
· Solubility in / Miscibility with			
water:	Not miscible or difficult to mix.		
· Partition coefficient (n-octanol/water): Not determined.			
· Viscosity:			
Dynamic:	Not determined.		
Kinematic:	Not determined.		

(Contd. on page 7)



Printing date 15.03.2013 Version number 3 Revision: 29.11.2011

Trade name: illbruck FM617

(Contd. of page 6)

Solvent content:

 VOC (EU)
 200.8 g/l

 VOC (EC)
 20.90 %

• **9.2 Other information** No further relevant information available.

## 10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- $\cdot$  Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

#### · LD/LC50 values relevant for classification:

### 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Oral	LD50	> 10000 mg/kg (rat)
Dermal	LD50	> 10000 mg/kg (rabbit)
Inhalative	LC50/4 h	ca. 0.493 mg/L (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

# 12 Ecological information

· 12.1 Toxicity

#### Aquatic toxicity:

### 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

EC50/24 h > 1000 mg/L (daphnia magna) LC0/96 h > 1000 mg/L (brachydanio rerio) NOEC/21 d > 10 mg/L (daphnia magna)

(Contd. on page 8)



Printing date 15.03.2013 Version number 3 Revision: 29.11.2011

Trade name: illbruck FM617

(Contd. of page 7)

- 12.2 Persistence and degradability No further relevant information available.
- Other information: The product is difficultly biodegradable.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

#### · Ecotoxical effects:

NOEC > 1000 mg/L (daphnia magna)

> 1000 mg/L (algae)

#### · Remark:

Using the previously mentioned tests, it can be proven that the ecotoxicological effects are very low. In keeping with the underlying regulations, the labeling was adjusted accordingly.

### Other information:

This product contains no substances in Annex I to Directive EC 2037/2000 concerning ozone depleting substances

- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

# · European waste catalogue

16 05 05 gases in pressure containers other than those mentioned in 16 05 04

15 01 04 metallic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

# **14 Transport information**

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· IMDG	AEROSOLS (alkanes, C14-17, chloro), MARINE POLLUTANT
·IATA	AEROSOLS, flammable

(Contd. on page 9)





Printing date 15.03.2013 Version number 3 Revision: 29.11.2011

Trade name: illbruck FM617

(Contd. of page 8)

# · 14.3 Transport hazard class(es)

· ADR





· Class 2 5F Gases.

· Label 2.1

· IMDG





· Class· Label2.1

·IATA



ClassLabel2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

• 14.5 Environmental hazards: Product contains environmentally hazardous

substances: alkanes, C14-17, chloro

· Marine pollutant: Yes

Symbol (fish and tree)

• Special marking (ADR): Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Gases.

· Danger code (Kemler):

• EMS Number: F-D.S-U

· 14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Tunnel restriction code

# 15 Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 1999/45/EC.

(Contd. on page 10)



Printing date 15.03.2013 Version number 3 Revision: 29.11.2011

Trade name: illbruck FM617

(Contd. of page 9)

- "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).
- "CHIP" SI 2009 No.716.
- "REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).
- "Aerosol" Regulation (EC) No 75/324.
- · National regulations:
- Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

	Re	leva	nt	ph	rases
--	----	------	----	----	-------

R64

**R66** 

Relevant p	phrases
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
R12	Extremely flammable.
R20	Harmful by inhalation.
	Harmful if swallowed.
	Irritating to eyes, respiratory system and skin.
R40	Limited evidence of a carcinogenic effect.
R42/43	May cause sensitisation by inhalation and skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.
D 0 4	

· Previous Revision Date: 17-01-2011 (UK)

· \* Data compared to the previous version altered.

May cause harm to breastfed babies.

Repeated exposure may cause skin dryness or cracking.