



CONTENTS

twinFLOOR is a waterproof, interlocking vinyl flooring range which consists of one decorative layer of vinyl bonded to a vinyl underlayer, both with overlapping gluestrips for easy assembly. Manufactured to EN 14041:2004

	twinFLOOR Tiles	twinFLOOR Planks
Unit Size	914 x 304 x 3.8mm	914 x 152 x 3.8mm
Units/pack	8	16
Pack Coverage	2.23m ²	2.23m ²
Weight	17kg	17kg

Colours	4 tile and 4 wood plank decors are available to order from stock.
Wear Layer	0.3mm
Surface	Aluminium Oxide abrasive coating
Slip Resistance	R10
Sound Reduction	DIN 55210 8db
Adhesive	Petroleum Pressure Sensitive adhesive is used on the gluestrips
Water Tightness	When submerged under 30mm water for 24 hours twinFLOOR meets EN 649 requirements.
Chemical Resistance	twinFLOOR exceeds EN 423:1993
Residual Indentation	twinFLOOR exceeds EN 433:1994
Accessories	<ul style="list-style-type: none"> - twinFLOOR Tape is available for repair and replacements. - twinFLOOR Polish and Cleaner is a 2-in-1 solution for protection and cleanliness

Cleaning & Maintenance

twinFLOOR can be swept, hoovered and mopped with a dilute neutral (pH 6-8) detergent. **twinFLOOR** polish and cleaner will help to protect the surface.